


# Community

# S-SERIES

# S-218S

## TWO-WAY FULL-RANGE LOUDSPEAKER SYSTEM



### Description

The S-218S is a professional subwoofer designed to complement and extend the low frequency output of any SONUS full-range loudspeaker.

Solidly constructed to ensure an accurate acoustic response that is uncolored by enclosure resonance, the rugged design of the S-218S handles the rigors of the road with ease.

The unit is characterized by a deep, powerful and compelling low frequency response that does not sacrifice speed of attack. The result is a rapid, punchy sonic signature coupled with sustained drive, enabling the 218S to easily handle most any musical challenge or special effects requirement.

Its high power and low distortion output provide accuracy and precision for musical styles including reggae, house, dance, ska, rock, metal and even dramatic classical productions.

The S-218S employs internal DYNA-TECH™ protection circuitry. Using only the power from the amplifier, DYNA-TECH actively prevents driver damage, even under severely abusive operating conditions.

Equipped with threaded rigging fittings, Ergo-Grip transport handles, integrated casters, and a stand receptacle that extends to the bottom of the enclosure for extra stability, the S-218S easily meets the demanding requirements of rental companies, touring musicians, Mobile DJs and other professional users.

### Applications

- **Clubs**
- **Concerts**
- **Touring**
- **Mobile DJ**
- **Themed Attractions**
- **Special Effects**

### Features

**Integrated Tilt-back Casters**

**DYNA-TECH™ Dynamic Protection**

**Switchable Hi-Pass / Parallel Output**

**Patented Cool-Coil™ Heat Evacuation Technology**

**Dual NL4 and Dual 1/4" Input / Output Connectors**

**Four M10 Threaded Rigging Fittings**

**Internal Stand Fitting Sleeved to Bottom of Enclosure for Stability**

### SYSTEM

- Format:** Subwoofer, vented bass - switchable hi-pass/parallel output
- Operating Range:** 30 Hz - 1 kHz
- Frequency Response:** 40 Hz - 200 Hz (±3 dB)
- Dispersion (-6 dB):** 360° H x 180° V
- Maximum SPL @1m:** 125 dB continuous / 132 dB peak
- High Pass Output:** 150 Hz (driving 8 ohm load). Switchable between Hi-Pass Out or Parallel Operation.
- Sensitivity in SPL: (1W/1m half space)** 100 dB (50 Hz - 160 Hz, 1/3 octave)
- Max Power Handling:** 600W RMS  
1500W Program / 2970W Peak
- Impedance:** Nominal 4Ω / Min. 3.2Ω at 120Hz

### TRANSDUCERS


- Low Frequency:** 2 x 18" (457mm) 300W RMS  
750W Program (each driver)

### MECHANICAL


- Enclosure:** 11-ply cross-laminated birch
- Finish:** Black catalyzed polyester paint
- Rigging Provisions:** Four M10 threaded rigging fittings<sup>1</sup> (two on each enclosure end)
- Grille:** Steel, powder coated black
- Dimensions:** 21.4" (544mm) x 44.4" (1128mm) x 24" (610mm)  
**H x W x D:**
- Net Weight:** 127 lbs / 57.6 kg

# S-218S

## TWO-WAY FULL-RANGE LOUDSPEAKER SYSTEM



### FREQUENCY RESPONSE



### IMPEDANCE

Note: Indicates the impedance of both drivers in parallel.

Recommended Power: 1200 to 1875 WRMS<sup>1</sup> at 4Ω

Recommended High-Pass Filter: 25 Hz, 24 dB/octave

<sup>1</sup>WRMS = Watts Root Mean Square

## Features & Accessories



**Padded Transport Covers**  
Protect your S-Series loudspeakers from scratches and mars.  
**Model CVR-S218S**



### Eyebolt Kit

Suspend your S-Series loudspeakers safely and easily.  
**Model M10EYBLTKIT**

### Support Stand

Elevates a full-range S-Series loudspeaker using the subwoofer as the base.  
**Model SB5**

**Integrated Casters Make Loading Easy**  
The S-218S Dual 18" Subwoofer is equipped with a pair of heavy-duty integral casters for ease of transport.



**Community Professional Loudspeakers, 333 East Fifth Street, Chester, PA USA 19013-4511**  
**TEL: 610-876-3400 • FAX: 610-874-0190 • www.communitypro.com**